



More Precision

optoNCDT // Laser displacement sensors (triangulation)






- *Non-contact and wear-free*
- *Large distance from the measurement object*
- *Small light spot for smallest parts*
- *Precise measurement results with high dynamics*
- *Almost independent of surface properties*

Measuring principle: laser triangulation

The sensor operates with a laser diode, which projects a visible light spot onto the measurement target. The light reflected from the spot is imaged by an optical receiving system onto a position-sensitive element. If the light spot changes its position, this change is imaged on the receiving element and evaluated. With the 1610 series, an analog PSD module is used as position-sensitive measuring element, whereas CMOS elements and CCD elements are used with the other high-performance sensors.



optoNCDT stands for high precision laser triangulation sensors

optoNCDT sensors are setting milestones for industrial laser displacement measurement. Micro-Epsilon laser sensors stand out due to size, measuring rate, software and, above all, due to precision. The current optoNCDT range now offers numerous series, each of which is amongst the best in its class.

Laser-based optical displacement sensors measure from a large distance to the target using a very small spot which enables measurements on the very small parts. The large measurement distance in turn enables measurements to be taken against difficult target surfaces such as hot metals. The non-contact principle enables wear-free measurements as the sensors are not subject to any physical contact with the target. Furthermore, the laser triangulation principle is ideal for very fast measurements with high accuracy and resolution.

Certified quality: calibration protocol

To document the performance capability of the optoNCDT sensors, each sensor is calibrated before delivery and supplied with its own calibration protocol. This document is supplied with the sensor and is used as proof to the achieved measurement precision.





							Page
General Information							
optoNCDT Technology							4 - 5
optoNCDT Application examples							6 - 7
	<i>Measuring range</i>	<i>Resolution / Repeatability</i>	<i>Linearity</i>	<i>Measuring rate</i>	<i>Laser</i>	<i>Targets</i>	
Compact Class							
optoNCDT 1220	10 - 50 mm	3.7 μm *	0.10 %	up to 1 kHz	red	all common targets	8 - 9
optoNCDT 1320	10 - 100 mm	1 μm *	0.10 %	up to 2 kHz	red		10 - 11
optoNCDT 1420	10 - 500 mm	0.5 μm *	from 0.08 %	up to 4 kHz	red		12 - 13
optoNCDT 1420 CL1	10 - 200 mm	0.5 μm *	from 0.08 %	up to 4 kHz	red class 1		14 - 15
High Speed PSD Sensor							
optoNCDT 1610 / 1630	4 - 100 mm	0.2 μm	0.2 %	up to 100 kHz	red	all common targets	16 - 17
Industry Standard							
optoNCDT 1750	2 - 750 mm	0.1 μm *	from 0.06 %	up to 7.5 kHz	red	all common targets	18 - 19
High Performance Sensors							
optoNCDT 2300	2 - 300 mm	0.03 μm	from 0.02 %	up to 49.14 kHz	red	all common targets	20 - 21
Sensors with Small Laser Line							
optoNCDT 1750LL	2 - 50 mm	0.1 μm *	from 0.06 %	up to 7.5 kHz	red	shiny / structured	22 - 23
optoNCDT 2300LL	2 - 50 mm	0.03 μm	from 0.02 %	up to 49.14 kHz	red		24 - 25
Long-Range Sensors							
optoNCDT 1710-50	50 mm	7.5 μm	0.1 %	up to 2.5 kHz	red	all common targets	26 - 27
optoNCDT 2310	10 - 50 mm	0.5 μm	0.03 %	up to 49.14 kHz	red		28 - 29
optoNCDT 1710 - 1000	1000 mm	100 μm	0.1 %	up to 2.5 kHz	red		30 - 31
Blue Laser Sensors							
optoNCDT 1710BL	50 / 1000 mm	1.5 μm	from 0.08 %	up to 2.5 kHz	blue	red-hot glowing / transparent / organic	32 - 33
optoNCDT 1750BL	20 - 750 mm	0.8 μm *	from 0.06 %	up to 7.5 kHz	blue		34 - 35
optoNCDT 2300BL	2 - 50 mm	0.03 μm	from 0.03 %	up to 49.14 kHz	blue		36 - 37
optoNCDT 2300-2DR	2 mm	0.03 μm	0.03 %	up to 49.14 kHz	blue	reflecting / transparent	38 - 39
Accessories							
Cables and protection housings							40 - 41
Interface converters and signal processing units							42 - 43
*corresponds to repeatability							

One of a kind:**Real Time Surface Compensation (RTSC) for maximum speed**

The unique RTSC function compensates for the amount of reflection from the target surface during continuous exposure and in real-time.

The exposure time or the amount of light produced by the laser is optimally matched to the reflection characteristics of the target surface.

All optoNCDT 17x0 and 2300 laser sensors are equipped with this innovative real-time control and therefore always achieve optimum results, even with rapidly changing surface types.



Comparison: optoNCDT with RTSC and conventional sensor

Unique ease of use via web interface

All optoNCDT 1320, 1420, 1750 and 2300 laser sensors are operated using an intuitive web interface. The sensor is connected to a PC. This web interface enables the user to make settings for the processing of measured values and signals, e.g. peak selection, filter and masking features for the video signal.

Designed for industrial applications

The sensors in the optoNCDT product range are designed for industrial applications. Due to their robust construction and technical features, they achieve precise measurement results even in harsh ambient conditions. Each series is available in a number of different measuring ranges which cover almost all common measuring distances.

Cables suitable for drag chain systems

All sensor cables for optoNCDT sensors are rated for use in drag chains and are therefore suitable for various fields of applications. Cables suitable for use with robots are available for any ILD series.

Compact with integrated controller


Despite their very compact dimensions, the ILD series have a fully integrated controller. As a result, simple, rapid installation and wiring is possible. The sensors can be integrated easily even into restricted installation space.

Adjustable filter functions

A number of filters are available in order to obtain optimum results for each application: moving average, recursive average and median. The filters are applied directly to the measurement results.

High measuring rates


High measuring rates are required for fast moving targets or measurements on difficult surfaces. Sensors in the 2300 Series achieve a measuring rate of up to 49 kHz. The analog 1630 high-speed series achieves measuring rates of up to 100 kHz.



Vibration measurement with moving average

Analog and digital output types

The optoNCDT sensors are equipped with different outputs to fulfil industrial user requirements. As well as analog interfaces, digital interfaces are also available for direct connection with the existing production environment. For further signal processing, interface converters and signal processing units are available.




Profile measurement with median



Innovative Sensors with Blue Laser Technology

The optoNCDT BL models are equipped with a blue laser diode and are used when standard sensors with a red laser diode are operating at their performance limits.

Due to its shorter wavelength, the blue laser does not penetrate the target surface, projecting a small light spot on the surface and therefore providing stable and precise results. This technology is preferably used with organic and (semi-)transparent objects, as well as for red-hot glowing metals.




The red laser penetrates the surfaces of some materials which produces a blurry image on the sensor element. Sensors with blue laser light do not penetrate the material and are imaged sharply onto the receiver element.

Synchronous measurement with multiple sensors


For many applications, it is necessary to measure or acquire data simultaneously using multiple sensors. Micro-Epsilon offers different signal processing units to support synchronized measurements. A „true synchronous“ measurement is required to precisely acquire moving or oscillating objects during thickness or differential measurements. In this case, one optoNCDT acts as the master, which provides the corresponding cycle pulse for the second sensor (slave). This function facilitates the genuine synchronous pulsing of two sensors.

[available for all 17x0 and 2300 models]

Synchronisation at thickness measurements of two sensors



Genuine synchronisation during thickness measurement using two optoNCDT sensors with simultaneous data acquisition




Conventional laser sensor with usual time offset erroneous measurement

Customer-specific sensor modifications

For applications where the above standard sensors do not meet your requirements, it is possible to supply a sensor with modified optical system, design or equipment. Please contact us - we will be pleased to advise you.

Options

- Modified offset and measuring range
- Custom housing or mounting geometry
- Optional interfaces
- Special cable length
- 90° beam deflection
- Vacuum suitability
- Reduced mass
- Increased shock and vibration resistance





Distance of vehicle to road surface

In road tests, pitching and rolling movements, spring compression during braking and other quantities are measured with optoNCDT sensors. optoNCDT is particularly suitable here due to its compact construction and the possibility of powering the sensor from the vehicle power supply.



Car body positioning in production lines

For automated processing of car bodies or vehicles, an exact determination of the position relative to the processing tool is necessary (drilling, punching, fitting, subassemblies). With its Real Time Surface Compensation, the optoNCDT sensor is ideally suited to the high-precision acquisition of painted surfaces.




Shape conformance on aluminum wheels

After casting, aluminum wheels are measured for a range of properties, e.g. hub depth, roundness and bulging.




Distance measurement in dispenser systems


Determining the exact distance value is a critical factor with dispensers for solder paste and adhesives. Compact laser sensors from Micro-Epsilon rapidly detect the exact distance from the printed circuit board.



Synchronous thickness measurement


optoNCDT sensors are ideally suited to the thickness measurement of a variety of (web) materials. Due to the high measuring rate and the possibility of synchronizing multiple sensors, even moving and oscillating targets can be reliably acquired.





Blue Laser Sensors for Dimensional Inspection

With certain measurement objects, the red laser beam penetrates the object. This effect does not occur with Blue Laser sensors as their laser point is sharply imaged onto the surface. Therefore, the sensors provide a stable and low-noise measurement signal. Blue Laser sensors are particularly suitable for detecting red-hot glowing metals as well as (semi-) transparent and organic materials.



Flatness measurement of IC pins

To achieve the best quality during board assembly, all IC pins must lie in one plane. In modern pick-and-place machines, the ICs are measured directly before placement. The tiny light spot diameters enable the measurement of the smallest pin geometries.


Package dimensions

In fully-automated logistics processes, the dimensions of packages are checked. Due to the large measuring range and the high measuring rate, compact laser sensors from Micro-Epsilon are used for automated, dimensional inspection.

optoNCDT LL for shiny metallic surfaces

The surface roughness of an object to be measured causes interferences in the laser point. This physical effect is particularly strong in shiny metallic objects and impedes an exact measurement.

optoNCDT LL (Laser Line) sensors compensate for this effect with an oval-shaped laser spot of just a few mm in width which is similar to a short 'laser line'. Interferences caused by surface roughness, defects, indentations or holes are filtered out using the oval-shaped light spot combined with special software algorithms. Furthermore, this type of sensor is suitable for distance measurements on structured surfaces i.e. when the distance to the surface and not the structure itself needs to be measured.






	Ideal for serial and OEM applications
	Compact design with integrated controller
	Measuring rate up to 1 kHz
	Analog output
	Plug & Play via select button
ATC	Auto Target Compensation

The optoNCDT 1220 is a new laser triangulation sensor with compact size for precise displacement, distance and position measurements. This sensor offers high accuracy and adjustable measuring rates up to 1 kHz.

Due to its extremely compact size with integrated controller, the sensor can also be installed in restricted spaces. Its low weight makes this laser sensor ideally suitable for applications where high accelerations occur e.g. on the robot gripper or in industrial printers.

The integrated Auto Target Compensation (ATC) provides stable distance signal control regardless of target color or brightness. Commissioning is quick and easy via function keys or the web interface.

The combination of compact design, versatility and measurement accuracy enables an excellent price/performance ratio, especially in OEM projects involving large quantities.



MR	SMR	Y
10	20	10
25	25	21
50	35	28

Model		ILD1220-10	ILD1220-25	ILD1220-50
Measuring range		10 mm	25 mm	50 mm
Start of measuring range		20 mm	25 mm	35 mm
Mid of measuring range		25 mm	37.5 mm	60 mm
End of measuring range		30 mm	50 mm	85 mm
Measuring rate ¹⁾		0.25 kHz / 0.5 kHz / 1 kHz		
Linearity		< ± 10 μm	< ± 25 μm	< ± 50 μm
		< ± 0.10 % FSO		
Repeatability ²⁾		< 3.7 μm	< 9.2 μm	< 18.4 μm
Temperature stability		± 0.03 % FSO / K		
Light spot diameter (± 10 %)	SMR	90 x 120 μm	100 x 140 μm	90 x 120 μm
	MMR	45 x 40 μm	120 x 130 μm	230 x 240 μm
	EMR	140 x 160 μm	390 x 500 μm	630 x 820 μm
	smallest diameter	45 x 40 μm with 24 mm	55 x 50 μm with 31 mm	70 x 65 μm with 42 mm
Light source		Semiconductor laser < 1 mW, 670 nm (red)		
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2015-07		
Permissible ambient light ³⁾		20,000 lx		
Supply voltage		11 ... 30 VDC		
Power consumption		< 2 W (24 V)		
Analog output		4 ... 20 mA (freely scalable within the measuring range)		
Switching output		1 x error output npn, pnp, push pull		
Connection		integrated cable 2 m, open ends, minimum bending radius 30 mm (fixed installation)		
Mounting		Screw connection via two mounting holes		
Temperature range	Storage	-20 ... +70 °C (non-condensing)		
	Operation	0 ... +50 °C (non-condensing)		
Shock (DIN-EN 60068-2-29)		15 g / 6 ms in 3 axes		
Vibration (DIN-EN 60068-2-6)		20 g / 20 ... 500 Hz		
Protection class (DIN-EN 60529)		IP65		
Material		Aluminum housing		
Weight		approx. 30 g (without cable), approx. 110 g (incl. cable)		
Control and display elements		Select button for zero / teach / factory settings web interface for setup ⁴⁾ 2 x 3 color LEDs for power and status		

FSO = Full Scale Output

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Factory setting 1 kHz; modifying the factory settings requires the IF2001/USB converter (optionally available)

²⁾ Measuring rate 1 kHz, median 9

³⁾ Illuminant: light bulb

⁴⁾ Connection to PC via IF2001/USB (optionally available)



- Ideal for serial and OEM applications**
- Compact design with integrated controller**
- Measuring rate up to 2 kHz**
- Analog and digital output**
- Trigger input and teach-in**
- Plug & Play via select button**
- Application-specific presets for fast sensor settings**
- ATC Auto Target Compensation**


The optoNCDT 1320 is very compact laser triangulation sensor intended for entry-level precision measurement tasks. This series is used to measure displacement, distance and position. The controller is integrated in the housing which considerably simplifies the installation procedure. Since the sensor is extremely compact, it can also be integrated into restricted installation space. Due to its low weight, the optoNCDT 1320 is ideally suitable for applications where high accelerations occur, e.g., on the robot arm or in pick-and-place machines.

Plug & Play with unique ease of use

The optoNCDT 1320 models enable quick sensor commissioning using the multifunction sensor button. An intuitive web interface offers extended sensor settings. The settings for the measurement task can be quickly selected via predefined presets. With the "Standard", "Changing surfaces" and "Material with penetration" settings, precise measurement results are easily achieved without any complex optimization. The quality slider enables the sensor to be adapted to static and dynamic processes.

The optoNCDT 1320 offers high accuracy and adjustable measuring rates up to 2 kHz, whereas the integrated Auto Target Compensation (ATC) provides stable distance signal control regardless of target color or brightness. Very small objects can be detected reliably due to the small and sharply projected measurement spot size.

MR	SMR	Y
10	20	10
25	25	21
50	35	28
100	50	46



Model		ILD1320-10	ILD1320-25	ILD1320-50	ILD1320-100
Measuring range		10 mm	25 mm	50 mm	100 mm
Start of measuring range	SMR	20 mm	25 mm	35 mm	50 mm
Mid of measuring range	MMR	25 mm	37.5 mm	60 mm	100 mm
End of measuring range	EMR	30 mm	50 mm	85 mm	150 mm
Linearity		$\leq \pm 10 \mu\text{m}$	$\leq \pm 25 \mu\text{m}$	$\leq \pm 50 \mu\text{m}$	$\leq \pm 100 \mu\text{m}$
		$\leq \pm 0.10 \% \text{ FSO}$			
Repeatability ¹⁾		1 μm	2.5 μm	5 μm	10 μm
Measuring rate ²⁾		0.25 kHz / 0.5 kHz / 1 kHz / 2 kHz			
Light source		Semiconductor laser < 1 mW, 670 nm (red)			
Permissible ambient light		30,000 lx			20,000 lx
Spot diameter $\pm 10 \%$	SMR	90 x 120 μm	100 x 140 μm	90 x 120 μm	750 x 1100 μm
	MMR	45 x 40 μm	120 x 130 μm	230 x 240 μm	
	EMR	140 x 160 μm	390 x 500 μm	630 x 820 μm	
	smallest diameter	45 x 40 μm with 24 mm	55 x 50 μm with 31 mm	70 x 65 μm with 42 mm	-
Protection class		IP65			
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2008-05			
Temperature stability		$\pm 0.03 \% \text{ FSO}/^\circ\text{C}$			
Operating temperature		0 ... +50 °C (non-condensing)			
Storage temperature		-20 ... +70 °C (non-condensing)			
Control inputs/outputs		1x HTL Laser on/off; 1 x HTL Multifunction input Trigger in / zero setting / mastering / teach (1x error output npn, pnp, push pull)			
Measurement value output	analog	4 ... 20 mA; 12 bit; freely scalable within the measuring range ³⁾			
	digital	RS422 / 16 bit			
Signal processing		14 bit			
Vibration		20 g / 20 ... 500 Hz (in accordance with IEC 60068-2-6)			
Shock		15 g / 6 ms / 3 axes (in accordance with IEC 60068-2-29)			
Weight	without cable	approx. 30 g			
	with 3 m cable	approx. 145 g			
Display		2 x 3 color LEDs for power and status			
Operation	Key	Select button for zero / teach / factory settings			
	Web interface	selectable presets ⁴⁾			
Supply voltage		11 ... 30 VDC			
Power consumption		< 2 W (24 V)			
Sensor cable		3 m integrated, open ends			
Controller		integrated signal processor			
Electromagnetic compatibility (EMC)		EN 61 000-6-3 / DIN EN 61326-1 (Class B) EN 61 000-6-2 / DIN EN 61326-1			

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Measuring rate 1 kHz, median 9; ²⁾ Factory setting 1 kHz; modifying the factory settings requires the IF2001/USB converter (optionally available);

³⁾ The D/A conversion is executed at 12 bit; ⁴⁾ Connection to PC via IF2001/USB (optionally available)



- Ideal for serial and OEM applications**
- Compact design with integrated controller**
- Measuring rate up to 4 kHz**
- Analog (U/I) and digital output**
- Trigger input / teach-in zero-setting / mastering**
- Configuration via web interface or Plug & Play**
- Application-specific presets and individual setups**
- ATC** **Auto Target Compensation**

The optoNCDT 1420 offers a unique combination of speed, size, performance and application versatility in the range of compact triangulation sensors. The sensor with integrated controller is used in restricted installation space or dynamic applications. The selectable connector type, i.e. cable or pigtail, together with compact size reduce the sensor installation effort to a minimum.

The Auto Target Compensation (ATC) provides stable distance signal control. The high-performance optical system projects the small light spot sharply onto the measurement object which enables to even detect smallest components and every little detail reliably.

Highest precision in a minimum of space

Compact size combined with low weight opens up new fields of application. Analog and digital output signals enable to integrate the sensor into plant or machine control systems. The triangulation sensor achieves a high measurement accuracy with measuring rates of up to 4 kHz.


Unique ease of use, individual results

All optoNCDT 1420 models are operated using an extended web interface. The settings for the measurement task can be quickly selected using predefined presets. The quality slider enables the sensor to be adapted to static and dynamic processes.

Up to eight user-specific sensor settings can be stored and exported in the setup management. The video signal display, the signal peak selection and a freely adjustable signal averaging enable to optimize the measurement task.

The ROI function (region of interest) allows e.g. for interfering signals in the background to be filtered out. The remaining signal peak is optimally corrected.

MR	SMR	Y
10	20	10
25	25	21
50	35	28
100	50	46
200	60	70
500	100	190



Model		ILD1420-10	ILD1420-25	ILD1420-50	ILD1420-100	ILD1420-200	ILD1420-500
Measuring range		10 mm	25 mm	50 mm	100 mm	200 mm	500 mm
Start of measuring range	SMR	20 mm	25 mm	35 mm	50 mm	60 mm	100 mm
Mid of measuring range	MMR	25 mm	37.5 mm	60 mm	100 mm	160 mm	350 mm
End of measuring range	EMR	30 mm	50 mm	85 mm	150 mm	260 mm	600 mm
Linearity		$\leq \pm 8 \mu\text{m}$	$\leq \pm 20 \mu\text{m}$	$\leq \pm 40 \mu\text{m}$	$\leq \pm 80 \mu\text{m}$	$\leq \pm 160 \mu\text{m}$	$\leq \pm 500 \mu\text{m}$
		$\leq \pm 0.08 \% \text{ FSO}$					$\leq \pm 0.1 \% \text{ FSO}$
Repeatability ¹⁾		0.5 μm	1 μm	2 μm	4 μm	8 μm	20 ... 40 μm
Measuring rate ²⁾		0.25 kHz / 0.5 kHz / 1 kHz / 2 kHz / 4 kHz					
Light source		Semiconductor laser < 1 mW, 670 nm (red)					
Permissible ambient light		50,000 lx			30,000 lx	10,000 lx	
Spot diameter $\pm 10 \%$	SMR	90 x 120 μm	100 x 140 μm	90 x 120 μm	750 x 1100 μm	750 x 1100 μm	750 x 1100 μm
	MMR	45 x 40 μm	120 x 130 μm	230 x 240 μm			
	EMR	140 x 160 μm	390 x 500 μm	630 x 820 μm	-	-	-
	smallest diameter	45 x 40 μm with 24 mm	55 x 50 μm with 31 mm	70 x 65 μm with 42 mm	-	-	-
Protection class		IP65					
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2008-05					
Temperature stability		$\pm 0.03 \% \text{ FSO}/^\circ\text{C}$					
Operating temperature		0 ... +50 $^\circ\text{C}$ (non-condensing)					
Storage temperature		-20 ... +70 $^\circ\text{C}$ (non-condensing)					
Control inputs/outputs		1x HTL Multifunction input Trigger in / zero setting / mastering / teach (1x error output npn, pnp, push pull) 1x HTL Laser on/off;					
Measurement value output	analog	4 ... 20 mA (1 ... 5 V with cable PCF1420-3/U); 12 bit; freely scalable within the measuring range ³⁾					
	digital	RS422 / 16 bit					
Vibration		20 g / 20 ... 500 Hz (in accordance with IEC 60068-2-6)					
Shock		15 g / 6 ms / 3 axes (in accordance with IEC 60068-2-29)					
Weight	with 3 m cable	approx. 145 g					
	with pigtail	approx. 60 g					
Display		2 x 3 color LEDs for power and status					
Operation	Key	Select button for zero / teach / factory settings					
	Web interface	application-specific presets; peak selection, video signal; freely selectable averaging possibilities; data reduction; setup management ⁴⁾					
Supply voltage		11 ... 30 VDC					
Power consumption		< 2 W (24 V)					
Sensor cable		3 m integrated, open ends					
		0.3 m pigtail with 12-pole M12 connector					
Controller		integrated signal processor					
Electromagnetic compatibility (EMC)		EN 61 000-6-3 / DIN EN 61326-1 (Class B)					
		EN 61 000-6-2 / DIN EN 61326-1					

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics);

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Measuring rate 2 kHz, median 9

²⁾ Factory setting 2 kHz; modifying the factory settings requires the IF2001/USB converter (optionally available)

³⁾ The D/A conversion is executed with 12 bit

⁴⁾ Connection to PC via IF2001/USB (optionally available)



- ≡ **Ideal for serial and OEM applications**
- ⚠ **Laser class 1**
- ⚙ **Compact design with integrated controller**
- 🕒 **Measuring rate up to 4kHz**
- A **Analog and digital output**
- T **Trigger input / teach-in zero-setting / mastering**
- 💻 **Configuration via web interface or Plug & Play**
- ATC **Auto Target Compensation**

optoNCDT CL1 laser sensors are used in measurement tasks which require laser class 1. With this laser class, the radiated power is at max. 390 μ W, which is significantly lower than laser class 2.

Use in automotive production


Particularly in the field of automotive production, increased demands are being placed on manufacturers to take adequate safety precautions in their production plants, including the use of laser class 1 sensors if people are working in close proximity to laser sensors. For example, this is the case when handling equipment for the attachment or installation of interior parts is used while laser sensors precisely align these parts.

Use in pharmaceutical and medical engineering

In medical engineering, laser sensors are often used to determine distances to very sensitive surfaces. Laser class 2 sensors can under certain circumstances cause a chemical or thermal reaction of the surface.

Here, optoNCDT 1420 CL1 sensors use only about one third of the energy of a laser class 2 sensor due to their reduced laser power of max. 390 μ W. This enables measurements of even sensitive materials such as substrates without causing any alterations of the target material.

MR	SMR	Y
10	20	10
25	25	21
50	35	28



Model		ILD1420-10CL1	ILD1420-25CL1	ILD1420-50CL1	ILD1420-100CL1	ILD1420-200CL1
Measuring range		10 mm	25 mm	50 mm	100 mm on request	200 mm on request
Start of measuring range	SMR	20 mm	25 mm	35 mm	-	-
Mid of measuring range	MMR	25 mm	37.5 mm	60 mm	-	-
End of measuring range	EMR	30 mm	50 mm	85 mm	-	-
Linearity ¹⁾		$\leq \pm 8 \mu\text{m}$	$\leq \pm 20 \mu\text{m}$	$\leq \pm 40 \mu\text{m}$	-	-
		$\leq \pm 0.08 \% \text{ FSO}$				
Repeatability ²⁾		0.5 μm	1 μm	2 μm	-	-
Measuring rate ³⁾		0.25 kHz / 0.5 kHz / 1 kHz / 2 kHz / 4 kHz				
Light source		Semiconductor laser < 0.39 mW, 670 nm (red)				
Permissible ambient light		15,000 lx			-	-
Spot diameter $\pm 10 \%$	SMR	90 x 120 μm	100 x 140 μm	90 x 120 μm	-	-
	MMR	45 x 40 μm	120 x 130 μm	230 x 240 μm	-	-
	EMR	140 x 160 μm	390 x 500 μm	630 x 820 μm	-	-
	smallest diameter	45 x 40 μm with 24 mm	55 x 50 μm with 31 mm	70 x 65 μm with 42 mm	-	-
Protection class		IP65				
Laser safety class		Class 1 in accordance with DIN EN 60825-1 : 2015-07				
Temperature stability		$\pm 0.03 \% \text{ FSO}/^\circ\text{C}$				
Operating temperature		0 ... +50 °C (non-condensing)				
Storage temperature		-20 ... +70 °C (non-condensing)				
Control inputs/outputs		1x HTL Multifunction input Trigger in / zero setting / mastering / teach (1x error output npn, pnp, push pull)				
Measurement value output	analog	4 ... 20 mA (1 ... 5 V with cable PCF1420-3/U); 12 bit; freely scalable within the measuring range ⁴⁾				
	digital	RS422 / 16 bit				
Vibration		20 g / 20 ... 500 Hz (in accordance with IEC 60068-2-6)				
Shock		15 g / 6 ms / 3 axes (in accordance with IEC 60068-2-29)				
Weight	with 3 m cable	approx. 145 g				
	with pigtail	approx. 60 g				
Display		2 x 3 color LEDs for power and status				
Operation	Key	Select button for zero / teach / factory settings				
	Web interface	application-specific presets; peak selection, video signal; freely selectable averaging possibilities; data reduction; setup management ⁵⁾				
Supply voltage		11 ... 30 VDC				
Power consumption		< 2 W (24 V)				
Sensor cable		3 m integrated, open ends				
		0.3 m pigtail with 12-pole M12 connector				
Controller		integrated signal processor				
Electromagnetic compatibility (EMC)		EN 61 000-6-3 / DIN EN 61326-1 (Class B) EN 61 000-6-2 / DIN EN 61326-1				

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics);

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Values apply from 0 - 50 % FSO or 50 - 100 % FSO; ²⁾ Measuring rate: 2 kHz, median 9;

³⁾ Factory setting 2 kHz; modifying the factory settings requires the IF2001/USB converter (optionally available)

⁴⁾ The D/A conversion is executed with 12 bit; ⁵⁾ Connection to PC via IF2001/USB (optionally available)




-  **Nine models with measuring ranges from 4 mm to 100 mm**
-  **Sensor head and separate controller**
-  **Up to 100 kHz (-3dB) true analog frequency response**
- INTER FACE** **Analog outputs (U/I) Ethernet**

Analog laser triangulation sensors of the optoNCDT 1610 and 1630 series are designed for extremely fast measurement processes. Equipped with a PSD array, the sensors automatically adapt to the reflection factor of the measurement object enabling measurements even on changing surfaces.


The LD 1610 series achieves a frequency response of 10 kHz (-3dB) while the LD 1630 series is suitable for measurements up to 100 kHz (-3dB).

Equipped with analog interfaces (current, voltage) and an optional Ethernet interface, the controller can be easily integrated into diverse systems.


Controller



optoNCDT 1610/1630 (4/10/20 mm)



optoNCDT 1610/1630 (50/100 mm)



MR	SMR	A
4	22	15
10	40	13.6
20	55	20.5
50	115	26.6
100	170	25.8

Sensors	LD1610-4	LD1610-10	LD1610-20	LD1610-50	LD1610-100
Measuring range	4 mm	10 mm	20 mm	50 mm	100 mm
Start of measuring range	22 mm	40 mm	55 mm	115 mm	170 mm
Linearity	$\leq \pm 8 \mu\text{m}$	$\leq \pm 20 \mu\text{m}$	$\leq \pm 40 \mu\text{m}$	$\leq \pm 100 \mu\text{m}$	$\leq \pm 200 \mu\text{m}$
	$\leq \pm 0.2 \% \text{ FSO}$				
Resolution (noise, dynamic ¹⁾)	2.6 μm	6.5 μm	13.0 μm	32.5 μm	65 μm
Resolution (noise, dynamic ²⁾)	0.2 μm	0.5 μm	1 μm	2.5 μm	6 μm
Spot diameter	0.3 mm	0.6 mm	0.9 mm	1.5 mm	1.5 mm
Frequency response	10 kHz (-3dB)				
Light source	Laser, wavelength 670 nm, red (visible)				
Laser safety class	Class 2				
Max. Vibration	10 g to 1 kHz (sensor head, 20 g optional)				
Operating temperature	0 ... +50 °C				
Storage temperature	-20 ... +70 °C				

Other measuring ranges on request ¹ Measurement on white target - Frequency response 10 kHz ² Measurement on white target - Frequency response 20 Hz

Sensors	LD1630-4	LD1630-10	LD1630-20	LD1630-50
Measuring range	4 mm	10 mm	20 mm	50 mm
Start of measuring range	22 mm	40 mm	55 mm	115 mm
Linearity	$\leq \pm 12 \mu\text{m}$	$\leq \pm 30 \mu\text{m}$	$\leq \pm 60 \mu\text{m}$	$\leq \pm 150 \mu\text{m}$
	$\leq \pm 0.3 \% \text{ FSO}$			
Resolution (noise, dynamic ¹⁾)	7 μm	17.5 μm	35 μm	50 μm
Resolution (noise, dynamic ²⁾)	0.4 μm	1 μm	2 μm	7.5 μm
Spot diameter	0.3 mm	0.6 mm	0.9 mm	1.5 mm
Frequency response	100 kHz (-3dB)			
Light source	Laser, wavelength 670 nm, red (visible)			
Laser safety class	Class 2			
Max. Vibration	5 g to 1 kHz (sensor head, 20 g optional)			
Operating temperature	0 ... +40 °C			
Storage temperature	-30 ... +75 °C			

Other measuring ranges on request ¹ Measurement on white target - Frequency response 100 kHz ² Measurement on white target - Frequency response 230 Hz

Controller		
Analog output	Distance	$\pm 10\text{V}$ (optional 0 ... 10 V / 0 ... 5 V) ; 4 ... 20 mA
	Output impedance	approx. 0 Ohm (10 mA max.)
	Tilt angle	with 30° object inclination (axis A): approx. 0.5% (white target)
	Frequency response	DC ... 10 kHz / 100 kHz
	Thermal drift	0.02 % °C FSO
	Light intensity	0 ... 10 V
Digital output	Ethernet (optional)	TCP/IP factory set IP 192.168.122.245 (sampling frequency 1 - 30 kHz)
Switching outputs with display	MIN	+24 V when distance < MIN, LED yellow
	OK	+24 V when distance > MIN and < MAX, LED green
	MAX	+24 V when distance > MAX, LED orange
	Error	+24 V, LED red
Switching hysteresis		approx. 0.5 % FSO
Permissible ambient light		20,000 lux
Operating time		50,000h (laser diode)
Insulation voltage		200 VDC, 0 V against housing
Humidity		up to 90% RH, non-condensing
Protection class		Sensor: IP64, controller: IP40
Supply voltage		10 ... 30 VDC
Max. current consumption		200 mA (24 V)
Connector		25-in D-sub
Sensor cable length, standard		2 m




-  **Compact design with integrated controller**
-  **Measuring rate up to 7.5 kHz**
-  **Analog and digital output**
-  **Trigger input/teach-in/zero-setting/mastering/synchronization**
-  **Configuration via web interface or Plug & Play**
-  **Application-specific presets and individual sensor settings**
-  **Real Time Surface Compensation**

The optoNCDT 1750 is a powerful laser triangulation sensor which is used in high speed, precise measurements in industrial applications. New evaluation algorithms and enhanced components provide highest accuracy and dynamics. The high-performance optical system generates a small light spot onto the target which enables to even detect smallest components reliably. Due to its compact size, the sensor can also be integrated into restricted installation spaces.


The optoNCDT 1750 laser stands out due to its real-time surface compensation feature. The real-time surface compensation feature (RTSC) determines the amount of reflection from the target surface during continuous exposure and in real-time. The exposure time or the amount of light produced by the laser is optimally matched to the reflection characteristics of the target surface. This enables extremely reliable measurements even on reflecting surfaces.

Different output signals enable to integrate the sensor into plant or machine control systems. As well as analog voltage and current outputs, a digital RS422 interface provides distance information from the sensor. All optoNCDT 1750 models are operated using an intuitive web interface. Due to the selectable setting and evaluation possibilities, the optoNCDT 1750 meets the requirements for use in industrial applications with high dynamics.

optoNCDT 1750 (2/10/20/50/100/200 mm)




optoNCDT 1750 (500/750 mm)




MR	SMR	Y
2	24	2
10	30	7
20	40	12
50	45	25
100	70	35
200	70	70
500	200	180
750	200	270

Connector (sensor side)



Connector (sensor cable)



Model	ILD1750-2	ILD1750-10	ILD1750-20	ILD1750-50	ILD1750-100	ILD1750-200	ILD1750-500	ILD1750-750
Measuring range	2 mm	10 mm	20 mm	50 mm	100 mm	200 mm	500 mm	750 mm
Start of measuring range	24 mm	30 mm	40 mm	45 mm	70 mm	70 mm	200 mm	200 mm
Mid of measuring range	25 mm	35 mm	50 mm	70 mm	120 mm	170 mm	450 mm	575 mm
End of measuring range	26 mm	40 mm	60 mm	95 mm	170 mm	270 mm	700 mm	950 mm
Linearity	$\leq \pm 1.6 \mu\text{m}$	$\leq \pm 6 \mu\text{m}$	$\leq \pm 12 \mu\text{m}$	$\leq \pm 30 \mu\text{m}$	$\leq \pm 60 \mu\text{m}$	$\leq \pm 160 \mu\text{m}$	$\leq \pm 350 \mu\text{m}$	$\leq \pm 670 \mu\text{m}$
	$\leq \pm 0.08 \%$ FSO	$\leq \pm 0.06 \%$ FSO				$\leq \pm 0.08 \%$ FSO	$\leq \pm 0.07 \%$ FSO	$\leq \pm 0.09 \%$ FSO
Repeatability ²⁾	0.1 μm	0.4 μm	0.8 μm	2 μm	4 μm	8 μm	20 μm	30 μm
Measuring rate	continuously adjustable 0.3 .. 7.5 kHz							
	6 adjustable stages: 7.5 kHz / 5 kHz / 2.5 kHz / 1.25 kHz / 625 Hz / 300 Hz							
Light source	Semiconductor laser < 1 mW, 670 nm (red)							
Permissible ambient light (with 2.5 kHz)	10,000 lx							
Laser safety class	Class 2 in accordance with DIN EN 60825-1 : 2015-07							
Spot diameter	SMR	80 μm	110 μm	320 μm	570 μm	740 μm	1300 μm	1500 μm
	MMR	35 μm	50 μm	45 μm	55 μm	60 μm	1300 μm	1500 μm
	EMR	80 μm	110 μm	320 μm	570 μm	700 μm	1300 μm	1500 μm
Temperature stability ¹⁾	0.025 % FSO/°C				0.01 % FSO/°C			
Operating temperature	0 ... +50 °C							
Storage temperature	-20 ... +70 °C							
Control inputs/outputs	1x HTL/TTL Laser on/off; 1x HTL/TTL multifunction input Trigger in / slave in / zero setting / mastering / teach 2x error outputs (error & limit value): npn, pnp, push pull) 1x RS422 synchronization input (trigger in, sync in, master/slave, master/slave alternating)							
Measurement value output	analog	4 ... 20 mA; 0 ... 5 V / 0 ... 10 V; 16 bit; freely scalable within the measuring range						
	digital	RS422 / 16 bit						
Operation	Keys	Select & function keys for interface selections, mastering (zero), teach, presets, quality slider, frequency selection, factory settings						
	Web interface	application-specific presets; peak selection, video signal; freely selectable averaging possibilities; data reduction; setup management ²⁾						
Supply voltage	11 ... 30 VDC							
Power consumption	< 3 W (24 V)							
Sensor cable	Standard	0.25 m pigtail with 14-pole ODU connector						
	Option	Extension: 3 / 10 m						
Synchronization	possible for simultaneous or alternating measurements							
Protection class	IP65							
Vibration	2 g / 20 ... 500 Hz							
Shock	15 g / 6 ms							
Weight (with 25 cm cable)	approx. 550 g						600 g	

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

¹⁾ Based on digital output

²⁾ Connection to PC via IF2001/USB (optionally available)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range




-  **Eight models with measuring ranges from 2 mm to 300 mm**
-  **Adjustable measuring rate up to 49.14 kHz**
- INTER FACE** **Ethernet / EtherCAT / RS422**
Analog output via C-Box
-  **Advanced Real Time Surface Compensation**
-  **Calibration certificate included**
-  **Measurement of diffuse and specular surfaces**
-  **Thickness measurement of transparent materials**
-  **Configuration via web interface**

The optoNCDT 2300 is the new, high performance version of Micro-Epsilon laser triangulation sensors and offers an adjustable measuring rate of up to 49.14 kHz. The entire electronics is already integrated in a compact sensor housing which is a worldwide unique feature of this sensor class. The new A-RTSC (Advanced Real Time Surface

Compensation) feature is a development of the already proven RTSC technology and, with its improved dynamic range, enables a more precise real time surface compensation during the measurement process. The threshold value of the compensation range can be easily configured via the software. Data output is via Ethernet, RS422 or


EtherCAT. The C-Box enables analog signal output. All sensor configurations are carried out via a user-friendly web interface. The optoNCDT 2300 is particularly used for high speed applications such as the monitoring of vibrations or measurements on challenging surfaces.

optoNCDT 2300-2 ... 2300-100
Diffuse reflection




MR	SMR	Y
2	24	1.5
5	24	3.5
10	30	6.5
20	40	10.0
50	45	23.0
100	70	33.5

optoNCDT 2300-2 ... 2300-20
Direct reflection



MR	SMR + 0.5 MR	α
2	25	20.5°
5	26.5	20.5°
10	35	17.5°
20	50	13.8°

optoNCDT 2300-200 /2300-300




MR	α	φ	ε	A	B
200	25.1°	16.7°	13.1°	91.6	76
300	18.3°	12.2°	9.6°	99.4	81

Model		ILD2300-2	ILD2300-5	ILD2300-10	ILD2300-20	ILD2300-50	ILD2300-100	ILD2300-200	ILD2300-300
Measuring range ¹⁾		2 (2) mm	5 (2) mm	10 (5) mm	20 (10) mm	50 (25) mm	100 (50) mm	200 (100) mm	300 (150) mm
Start of measuring range	SMR	24 (24) mm	24 (24) mm	30 (35) mm	40 (50) mm	45 (70) mm	70 (120) mm	130 (230) mm	200 (350) mm
Mid of measuring range	MMR	25 (25) mm	26.5 (25) mm	35 (37.5) mm	50 (55) mm	70 (82.5) mm	120 (145) mm	230 (280) mm	350 (425) mm
End of measuring range	EMR	26 (26) mm	29 (26) mm	40 (40) mm	60 (60) mm	95 (95) mm	170 (170) mm	330 (330) mm	500 (500) mm
Linearity		$\leq \pm 0.6 \mu\text{m}$	$\leq \pm 1.5 \mu\text{m}$	$\leq \pm 2 \mu\text{m}$	$\leq \pm 4 \mu\text{m}$	$\leq \pm 10 \mu\text{m}$	$\leq \pm 20 \mu\text{m}$	$\leq \pm 60 \mu\text{m}$	$\leq \pm 90 \mu\text{m}$
		$\leq \pm 0.03 \%$ FSO		$\leq \pm 0.02 \%$ FSO		$\leq \pm 0.02 \%$ FSO		$\leq \pm 0.03 \%$ FSO	
Resolution (with 20 kHz)		0.03 μm	0.08 μm	0.15 μm	0.3 μm	0.8 μm	1.5 μm	3 μm	4.5 μm
Measuring rate		switchable (software) 49.14 / 30 / 20 / 10 / 5 / 2.5 / 1.5 kHz (49.14 kHz with reduced measuring range)							
Permissible ambient light		10,000 ... 40,000 lx							
Spot diameter	SMR	55 x 85 μm	70 x 80 μm	75 x 85 μm	140 x 200 μm	255 x 350 μm	350 μm	1300 μm	580 x 860 μm
	MMR	23 x 23 μm	30 x 30 μm	32 x 45 μm	46 x 45 μm	70 x 70 μm	130 μm	1300 μm	380 x 380 μm
	EMR	35 x 85 μm	70 x 80 μm	110 x 160 μm	140 x 200 μm	255 x 350 μm	350 μm	1300 μm	470 x 530 μm
Light source		Laser diode (670 nm) class 2							
Protection class		IP65							
Operating temperature		0 ... +50 °C							
Storage temperature		-20 ... +70 °C							
Inputs/Outputs		Ethernet/EtherCAT RS422 analog output via C-Box							
Inputs		Laser on/off Sync/Trigger input							
Supply voltage		11 ... 30 VDC							
Power consumption		< 3 W (24 V)							
LED		status / power / Ethernet / EtherCAT							
Sensor cable	Standard	0.25 m (with connector)							
	Option	3 / 6 / 9 m with 15-pole sub-D Connector							
Synchronization		possible for simultaneous or alternating measurements							
Electromagnetic compatibility (EMC)		EN 61326-1: 2006-10 DIN EN 55011: 2007-11 (group 1, class B) EN 61 000-6-2: 2006-03							
Vibration		2 g / 20 ... 500 Hz							
Shock		15 g / 6 ms / 3 axes							

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Range specifications: value in brackets is valid for a measuring rate of 49.14 kHz







-  **Laser Line averages across shiny metallic or structured surfaces**
-  **Four models with measuring ranges from 2 mm to 50 mm**
-  **Real Time Surface Compensation**
-  **Adjustable measuring rate up to 7.5 kHz**
-  **Analog (U/I) and digital output**
-  **Adjustable filter functions (firmware)**
-  **High flex cables for dragchain or robot use**
-  **Calibration certificate included**

The compact optoNCDT 1750LL is perfectly suitable for measurements against shiny and structured surfaces. The point-shaped laser beam is widened using a lens to form an oval point. Therefore, physically induced interferences can be easily filtered enabling measurements on shiny surfaces. Due to its compact size, the sensor can easily be integrated into restricted installation space.




optoNCDT 1750LL (2/10/20/50 mm)



Connector (sensor side)



Connector (sensor cable)



MR	SMR	Y
2	24	2
10	30	7
20	40	12
50	45	25

Model		ILD1750-2LL	ILD1750-10LL	ILD1750-20LL	ILD1750-50LL
Measuring range		2 mm	10 mm	20 mm	50 mm
Start of measuring range		24 mm	30 mm	40 mm	45 mm
Mid of measuring range		25 mm	35 mm	50 mm	70 mm
End of measuring range		26 mm	40 mm	60 mm	95 mm
Linearity		$\leq \pm 1.6 \mu\text{m}$	$\leq \pm 6 \mu\text{m}$	$\leq \pm 12 \mu\text{m}$	$\leq \pm 30 \mu\text{m}$
		$\leq \pm 0.08 \%$ FSO	$\leq \pm 0.06 \%$ FSO		
Repeatability ²⁾		0.1 μm	0.4 μm	0.8 μm	2 μm
Measuring rate		continuously adjustable 0.3 .. 7.5 kHz			
		6 adjustable stages: 7.5 kHz / 5 kHz / 2.5 kHz / 1.25 kHz / 625 Hz / 300 Hz			
Light source		Semiconductor laser < 1 mW, 670 nm (red)			
Permissible ambient light with 2.5 kHz		10,000 lx			
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2008-05			
Spot diameter	SMR	85 x 240 μm	120 x 405 μm	185 x 485 μm	350 x 320 μm
	MMR	24 x 280 μm	35 x 585 μm	55 x 700 μm	70 x 960 μm
	EMR	64 x 400 μm	125 x 835 μm	195 x 1200 μm	300 x 1940 μm
Temperature stability ¹⁾		0.025 % FSO/°C	0.01 % FSO/°C		
Operating temperature		0 ... +50 °C			
Storage temperature		-20 ... +70 °C			
Control inputs/outputs		1x HTL/TTL Laser on/off; 1x HTL/TTL multifunction input Trigger in / slave in / zero setting / mastering / teach 2x error outputs (error & limit value): npn, pnp, push pull) 1x RS422 synchronization input (trigger in, sync in, master/slave, master/slave alternating)			
Measured value output	analog	4 ... 20 mA; 0 ... 5 V / 0 ... 10 V; 16 bit; freely scalable within the measuring range			
	digital	RS422 / 16 bit			
Operation	Keys	Select & function keys for interface selections, mastering (zero), teach, presets, quality slider, frequency selection, factory settings			
	Web interface	application-specific presets; peak selection, video signal; freely selectable averaging possibilities; data reduction; setup management ²⁾			
Supply voltage		11 ... 30 VDC			
Power consumption		< 3 W (24 V)			
Sensor cable	Standard	0.25 m pigtail with 14-pole ODU connector			
	Option	Extension: 3 / 10 m			
Synchronization		possible for simultaneous or alternating measurements			
Protection class		IP65			
Vibration		2 g / 20 ... 500 Hz			
Shock		15 g / 6 ms			
Weight (with 25cm cable)		approx. 550 g			

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

¹⁾ Based on digital output

²⁾ Connection to PC via IF2001/USB (optionally available)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range





-  **Laser Line averages across shiny metallic or structured surfaces**
-  **Four models with measuring ranges from 2 mm to 50 mm**
-  **Adjustable measuring rate up to 49.14 kHz**
312Hz
375Hz
1000Hz
- INTER FACE** **Ethernet / EtherCAT / RS422**
Analog output via C-Box
-  **Advanced Real-Time-Surface-Compensation**
-  **Calibration certificate included**
-  **Configuration via web interface**

The optoNCDT 2300LL is ideally suitable for measurements against shiny and structured surfaces. The point-shaped laser beam is widened using a lens to form an oval point. Therefore, physically induced interferences can be easily filtered enabling measurements on shiny surfaces. Due to its compact size, the sensor can easily be integrated into restricted installation space.

The "Advanced Real Time Surface Compensation" (A-RTSC), with its improved dynamic range, enables a more precise real time surface compensation during the measurement process. Data output is via Ethernet, RS422 or EtherCAT. All sensor configurations are carried out via a user-friendly web interface.

optoNCDT 2300LL



MR	SMR	Y
2	24	1.5
10	30	6.5
20	40	10.0
50	45	23.0

Model		ILD2300-2LL	ILD2300-10LL	ILD2300-20LL	ILD2300-50LL
Measuring range ¹⁾		2 (2) mm	10 (5) mm	20 (10) mm	50 (25) mm
Start of measuring range	SMR	24 (24) mm	30 (35) mm	40 (50) mm	45 (70) mm
Mid of measuring range	MMR	25 (25) mm	35 (37.5) mm	50 (55) mm	70 (82.5) mm
End of measuring range	EMR	26 (26) mm	40 (40) mm	60 (60) mm	95 (95) mm
Linearity		$\leq \pm 0.6 \mu\text{m}$	$\leq \pm 2 \mu\text{m}$	$\leq \pm 4 \mu\text{m}$	$\leq \pm 10 \mu\text{m}$
		$\leq \pm 0.03 \% \text{ FSO}$	$\leq \pm 0.02 \% \text{ FSO}$		
Resolution (with 20 kHz)		0.03 μm	0.15 μm	0.3 μm	0.8 μm
		0.0015 % FSO			
Measuring rate		switchable (software) 49.14 / 30 / 20 / 10 / 5 / 2.5 / 1.5 kHz (49.14 kHz with reduced measuring range)			
Permissible ambient light		10,000 ... 40,000 lx			
Spot diameter	SMR	85 x 240 μm	120 x 405 μm	185 x 485 μm	350 x 320 μm
	MMR	24 x 280 μm	35 x 585 μm	55 x 700 μm	70 x 960 μm
	EMR	64 x 400 μm	125 x 835 μm	195 x 1200 μm	300 x 1940 μm
Light source		Laser diode (670 nm) class 2			
Protection class		IP65			
Operating temperature		0 ... +50 °C			
Storage temperature		-20 ... +70 °C			
Inputs/Outputs		Ethernet/EtherCAT RS422 analog output via C-Box			
Inputs		Laser on/off Sync/Trigger input			
Supply voltage		11 ... 30 VDC			
Power consumption		< 3 W (24 V)			
LED		status / power / Ethernet / EtherCAT			
Sensor cable	Standard	0.25 m (with connector)			
	Option	3 / 6 / 9 m with 15-pole sub-D Connector			
Synchronization		possible for simultaneous or alternating measurements			
Electromagnetic compatibility (EMC)		EN 61326-1: 2006-10 DIN EN 55011: 2007-11 (group 1, class B) EN 61 000-6-2: 2006-03			
Vibration		2 g / 20 ... 500 Hz			
Shock		15 g / 6 ms / 3 axes			

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Range specifications: value in brackets is valid for a measuring rate of 49.14 kHz




-  **High accuracy and long standoff distances**
-  **Adjustable measurement rate up to 2.5 kHz**
-  **Real Time Surface Compensation**
-  **Analog and digital output**
-  **Adjustable filter functions (firmware)**
-  **Calibration certificate included**

The optoNCDT 1710-50 long-range laser sensors are designed for large measurement distances combined with high precision. They operate according to the triangulation and measure distances without contact on a wide range of material surfaces.

Unlike conventional laser triangulation sensors, the long-range series measures over a large measurement distance and is therefore better protected against possible collisions. The integrated Real Time Surface Compensation enables measurements even on changing surfaces.

optoNCDT 1710-50 (50 mm)



(Dimensions in mm, not to scale.)

Model	ILD1710-50	
Measuring range	50 mm	
Start of measuring range	550 mm	
Mid of measuring range	575 mm	
End of measuring range	600 mm	
Linearity	$\leq \pm 50 \mu\text{m}$	
	$\leq \pm 0.1 \% \text{ FSO}$	
Resolution	7.5 μm	
	0.015% FSO (at 2.5 kHz without averaging)	
Measuring rate	2.5 kHz / 1.25 kHz / 625 Hz / 312.5 Hz (adjustable)	
Permissible ambient light	10,000 lx	
Light spot diameter	SMR	400 x 500 μm
	MMR	400 x 500 μm
	EMR	400 x 500 μm
Light source	Semiconductor laser < 1 mW, 670 nm (red)	
Laser safety class	Class 2 in accordance with DIN EN 60825-1 : 2008-05	
Protection class	IP65	
Temperature stability	0.01 % FSO/°C	
Operating temperature	0 ... +50 °C	
Storage temperature	-20 ... +70 °C	
Output	analog	4 ... 20 mA (0 ... 10 V)
	digital	RS422 / USB (optional with cable PC1700-3/USB)
	Switching outputs	1 x error or 2x limit values (configurable)
Switching input	Laser ON-OFF / Zero	
Operation	via membrane keypad on sensor or via PC with ILD 1700 tool	
Supply voltage	11 ... 30 VDC	
Max. current consumption	150 mA (24 V)	
Sensor cable	standard: 0.25 m - integrated	
Synchronization	possible for simultaneous or alternating measurements	
Vibration	2 g / 20 ... 500 Hz	
Shock	15 g / 6 ms	
Weight	Sensor	approx. 800 g

FSO = Full Scale Output; All specifications apply for a diffusely reflecting matt white ceramic target;
SMR = start of measuring range MMR = midrange EMR = end of measuring range




-  **High accuracy and long standoff distances**
-  **Four models with measuring ranges from 10 mm to 50 mm**
-  **Adjustable measuring rate up to 49.14 kHz**
312Hz
375Hz
1000Hz
- INTER FACE** **Ethernet / Ethercat / RS422**
Analog output via C-Box
-  **Advanced Real-Time-Surface-Compensation**
-  **Calibration certificate included**
-  **Configuration via web interface**


The optoNCDT 2310 long-range laser sensors are designed for large measurement distances combined with high precision.

They operate according to the triangulation and measure distances without contact on a wide range of material surfaces. Unlike conventional laser triangulation sensors, the long-range series measures over a large measurement distance and is therefore better protected against possible collisions. The integrated Real Time Surface Compensation enables measurements even on changing surfaces.

optoNCDT 2310-10/2310-20/2310-40



optoNCDT 2310-50



(Dimensions in mm, not to scale.)

Model		ILD2310-10	ILD2310-20	ILD2310-40	ILD2310-50
Measuring range ¹⁾		10 (5) mm	20 (10) mm	40 (20) mm	50 (25) mm
Start of measuring range		95 (100) mm	90 (100) mm	175 (195) mm	550 (575) mm
Mid of measuring range		100 (102.5) mm	100 (105) mm	195 (205) mm	575 (587.5) mm
End of measuring range		105 (105) mm	110 (110) mm	215 (215) mm	600 (600) mm
Linearity		$\leq \pm 3 \mu\text{m}$	$\leq \pm 6 \mu\text{m}$	$\leq \pm 12 \mu\text{m}$	$\leq \pm 50 \mu\text{m}$
		$\leq \pm 0.03 \%$ FSO	$\leq \pm 0.03 \%$ FSO	$\leq \pm 0.03 \%$ FSO	$\leq \pm 0.1 \%$ FSO
Resolution		0.5 μm	1 μm	2 μm	7.5 μm
		0.005 % FSO	0.005 % FSO (at 10 kHz without averaging)	0.005 % FSO	0.015 % FSO
Measuring rate		switchable (software) 49.14 / 30 / 20 / 10 / 5 / 2.5 / 1.5 kHz (49.14 kHz with reduced measuring range)			
Permissible ambient light		10,000...40,000 lx			
Light spot diameter	SMR	400 x 500 μm	200 μm	230 μm	400 ... 500 μm
	MMR	400 x 500 μm	60 μm	210 μm	400 ... 500 μm
	EMR	400 x 500 μm	200 μm	230 μm	400 ... 500 μm
Light source		laser diode (670nm) class 2			
Protection class		IP65			
Operating temperature		0 ... +50 °C			
Storage temperature		-20 ... +70 °C			
Inputs/Outputs		Ethernet/EtherCAT RS422 analog output via C-Box			
Inputs		Laser on/off Sync/Trigger input			
Supply voltage		11 ... 30 VDC			
Power consumption		< 3 W (24 V)			
LED		status / power / Ethernet / EtherCAT			
Sensor cable		standard: 0.25 m - integrated			
Synchronization		possible for simultaneous or alternating measurements			
Electromagnetic compatibility (EMC)		EN 61326-1: 2006-10 DIN EN 55011: 2007-11 (group 1, class B) EN 61 000-6-2: 2006-03			
Vibration		2 g / 20 ... 500 Hz			
Shock		15 g / 6 ms / 3 axes			

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Range specifications: value in brackets is valid for a measuring rate of 49.14 kHz

Model		ILD1710-1000
Measuring range		1000 mm
Start of measuring range (offset distance)		1000 mm
Mid of measuring range		1500 mm
End of measuring range		2000 mm
Linearity		≤ ± 1 mm
		≤ ± 0.1% FSO
Resolution (at 2.5 kHz without averaging)		100 μm
Measuring rate		2.5 kHz / 1.25 kHz / 625 Hz / 312.5 Hz (adjustable)
Light source		Semiconductor laser < 1 mW, 670 nm (red)
Permissible ambient light	at 2.5 kHz	10,000 lx
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2008-05
Light spot diameter	SMR	2.5 ... 5 mm
	MMR	2.5 ... 5 mm
	EMR	2.5 ... 5 mm
Temperature stability		0.01% FSO/°C
Operating temperature		0 ... +50 °C
Storage temperature		-20 ... +70 °C
Output	Measured values	switchable: 4 ... 20 mA / 0 ... 10 V / RS422 / USB (optional via cable PC1700-3/USB)
	Switching outputs	1 x error or 2x limit values (configurable)
Switching input		Laser ON-OFF / Zero
Operation		via membrane keypad on sensor or via PC with ILD 1700 tool
Supply voltage		11 ... 30 VDC
Max. current consumption		150 mA (24 V)
Sensor cable		standard 0.25 m integrated
Synchronization		possible for simultaneous or alternating measurements
Protection class		IP65
Vibration		2 g / 20 ... 500 Hz
Shock		15 g / 6 ms
Weight		~ 0.8 kg

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range





-  **Two models with measuring ranges from 50 mm and 1000 mm**
-  **Blue Laser Technology (Blue violet laser diode 405 nm)**
-  **Real Time Surface Compensation**
-  **Adjustable measuring rate up to 2.5 kHz**
-  **Analog (U/I) and digital output**
-  **Adjustable filter functions**
-  **High flex cables for dragchain or robot use**
-  **Calibration certificate included**

Equipped with a blue-violet laser diode (405 nm), the optoNCDT 1710BL sensor achieves high accuracies on red-hot glowing metals and organic materials.

In numerous applications, Blue Laser sensors are superior to standard sensors that use a red laser diode. In contrast to a red laser, the reduced wavelength of the blue laser light does not penetrate materials such as wood, skin and foods. The blue laser generates a minimal laser point on the surface and therefore offers more stable, precise measurements.

The inner workings of the Blue Laser triangulation sensor are a complete re-design. The sensors are equipped with new high-end lenses, new intelligent laser control and evaluation algorithms.


optoNCDT 1710 (50/1000 mm)




Start Measuring range

Measuring range

Connector (sensor side)



Connector (sensor cable)



Model	ILD1710-50BL	ILD1710-1000BL	
Measuring range	50 mm	1000 mm	
Start of measuring range	550 mm	1000 mm	
Mid of measuring range	575 mm	1500 mm	
End of measuring range	600 mm	2000 mm	
Linearity	$\leq \pm 50 \mu\text{m}$	$\leq \pm 1 \text{ mm}$	
	$\leq \pm 0.1\% \text{ FSO}$	$\leq \pm 0.1\% \text{ FSO}$	
Resolution (at 2.5 kHz without averaging)	5 μm	100 μm	
Measuring rate	2.5 kHz / 1.25 kHz / 625 Hz / 312.5 Hz (adjustable)		
Light source	Semiconductor laser <1 mW, 405nm (blue violet), laser class 2		
Permissible ambient light (with 2.5 kHz)	10,000 lx		
Laser safety class	Class 2 in accordance with DIN EN 60825-1 : 2008-05		
Spot diameter	SMR	400 x 500 μm	2.5...5 mm
	MMR	400 x 500 μm	2.5...5 mm
	EMR	400 x 500 μm	2.5...5 mm
Temperature stability ¹⁾	0.01% FSO/°C		
Operating temperature	0 ... +50 °C		
Storage temperature	-20 ... +70 °C		
Output	Measured values	switchable: 4 ... 20 mA / 0 ... 10 V / RS422 / USB (optional via cable PC1700-3/USB)	
	Switching outputs	1 x error or 2x limit values (configurable)	
Switching input	Laser ON-OFF / Zero		
Operation	via membrane keypad on sensor or via PC with ILD 1700 tool		
Supply voltage	11 ... 30 VDC		
Max. current consumption	150 mA (24 V)		
Sensor cable (with connector)	standard 0.25 m integrated / option: 3 m or 10 m extensions		
Synchronization	possible for simultaneous or alternating measurements		
Protection class	IP65		
Vibration	2 g / 20 ... 500 Hz		
Shock	15 g / 6 ms		
Weight (with 25 cm cable)	approx. 800 g	approx. 800 g	

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

¹⁾ Based on digital output

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range




-  **Four models with measuring ranges from 20 mm bis 750 mm**
-  **Blue Laser Technology (Blue violet laser diode 405 nm)**
-  **Real Time Surface Compensation**
-  **Adjustable measuring rate up to 7.5 kHz**
-  **Analog and digital output**
-  **Trigger input/teach-in/zero-setting/mastering/synchronization**
-  **Configuration via web interface or Plug & Play**
-  **Application-specific presets and individual setups**

Blue Laser sensors in the optoNCDT 1750BL series are designed for high speed displacement, distance and position measurements. These sensors are equipped with new high performance lenses, laser control and evaluation algorithms to ensure precise measurements on different surfaces and materials.


The Blue Laser technology patented by Micro-Epsilon offers decisive advantages compared to red-diode laser sensors. Since the blue laser point does not penetrate the surface, the target is sharply imaged onto the sensor element. This makes it possible to achieve high resolution and reliable signal stability.

optoNCDT 1750BL (20/200 mm)



MR	SMR	Y
20	40	12
200	70	70
500	200	180
750	200	270

optoNCDT 1750BL (500/750 mm)



(Dimensions in mm, not to scale)

Model		ILD1750-20BL	ILD1750-200BL	ILD1750-500BL	ILD1750-750BL
Measuring range		20 mm	200 mm	500 mm	750 mm
Start of measuring range		40 mm	70 mm	200 mm	200 mm
Mid of measuring range		50 mm	170 mm	450 mm	575 mm
End of measuring range		60 mm	270 mm	700 mm	950 mm
Measuring rate ¹⁾		continuously adjustable between 0.3 ... 7.5 kHz; 6 adjustable stages: 300 Hz / 625 Hz / 1.25 kHz / 2.5 kHz / 5 kHz / 7.5 kHz			
Linearity		< ± 12 µm	< ± 160 µm	< ± 350 µm	< ± 670 µm
		< ± 0.06 % FSO	< ± 0.08 % FSO	< ± 0.07 % FSO	< ± 0.09 % FSO
Repeatability ²⁾		< 0.8 µm	< 15 µm	< 20 µm	< 45 µm
Temperature stability ³⁾		± 0.03 % FSO / K			
Light spot diameter (± 10 %)	SMR	320 µm	1300 µm	1500 µm	1500 µm
	MMR	45 µm			
	EMR	320 µm			
Light source		Semiconductor laser < 1 mW, 405 nm (blue violet)			
Laser safety class		Class 2 in accordance with DIN EN 60825-1 : 2015-07			
Permissible ambient light		10,000 lx			
Supply voltage		11 ... 30 VDC			
Power consumption		< 3 W (24 V)			
Signal input		1x HTL/TTL multi-function input input trigger in / slave in, zero setting / mastering / teach-in; 1 x RS422 synchronization input trigger in / sync in / master slave / master slave alternating			
Digital interface		RS422 (16 bit)			
Analog output		4 ... 20 mA / 0 ... 5 V / 0 ... 10 V (16 bit, freely scalable within the measuring range)			
Switching output		1 x HTL/TTL laser on/off; 2 x switching output (error & limit value): npn, pnp, push pull			
Synchronization		possible for simultaneous or alternating measurements			
Connection		integrated pigtail 0.25 m with 14-pin ODU plug; optional extension to 3 m / 10 m			
Mounting		Screw connection via three mounting holes			
Temperature range	Storage	-20 ... +70 °C			
	Operation	0 ... +50 °C			
Shock (DIN-EN 60068-2-29)		15 g / 6 ms in 3 axes			
Vibration (DIN-EN 60068-2-6)		2 g / 20 ... 500 Hz			
Protection class (DIN-EN 60529)		IP65			
Material		Die-cast zinc housing		Aluminum housing	
Weight		approx. 550 g (incl. pigtail)			approx. 600 g (incl. pigtail)
Control and display elements		Select & function keys for interface selections, mastering (zero), teach, presets, quality slider, frequency selection, factory settings; Web interface with application-specific presets; peak selection, video signal; freely selectable averaging possibilities; data reduction; setup management ⁴⁾			

FSO = full scale output, SMR = start of measuring range, MMR = mid of measuring range, EMR = end of measuring range

The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

¹⁾ Factory setting 5 kHz; modifying the factory settings requires the IF2001/USB converter (optionally available)

²⁾ Measuring rate 5 kHz, median 9

³⁾ Based on digital output


⁴⁾ Connection to PC via IF2001/USB (optionally available)



-  **Three models with measuring ranges from 2 mm to 50 mm**
-  **Blue Laser Technology (Blue violet laser diode 405 nm)**
-  **Adjustable measuring rate up to 49.14 kHz**
- INTER FACE** **Ethernet / Ethercat / RS422**
Analog output via C-Box
-  **Advanced Real-Time-Surface-Compensation**
-  **Calibration certificate included**
-  **Measurement of diffuse and specular surfaces**
-  **Configuration via web interface**


Blue Laser sensors in the optoNCDT 2300BL series are designed for high speed displacement, distance and position measurements on red-hot glowing metals and organic materials. In numerous applications, Blue Laser sensors are superior to standard sensors that use a red laser diode. In contrast to a red laser, the blue-violet laser light does not penetrate materials such as wood, skin and foods. The blue laser generates a minimal laser point on the surface and therefore offers more stable, precise measurements.

optoNCDT 2310-50BL




(Dimensions in mm, not to scale.)

optoNCDT 2300-2BL / 2300-5BL
Diffuse reflection



MR	SMR	Y
2	24	1.5
5	24	3.5

optoNCDT 2300-2BL / 2300-5BL
Direct reflection



MR	SMR + 0.5 MR	α
2	25	20.5°
5	26.5	20°

Model		ILD2300-2 BL	ILD2300-5 BL	ILD2310-50 BL
Measuring range ¹⁾		2 (2) mm	5 (2) mm	50 (25) mm
Start of measuring range	SMR	24 (24) mm	24 (24) mm	550 (575) mm
Mid of measuring range	MMR	25 (25) mm	26.5 (25) mm	575 (587.5) mm
End of measuring range	EMR	26 (26) mm	29 (26) mm	600 (600) mm
Linearity		$\leq \pm 0.6 \mu\text{m}$	$\leq \pm 1.5 \mu\text{m}$	$\leq \pm 40 \mu\text{m}$
		$\leq \pm 0.03 \% \text{ FSO}$		$\leq \pm 0.08 \% \text{ FSO}$
Resolution (with 20 kHz)		$0.03 \mu\text{m}$	$0.08 \mu\text{m}$	$7.5 \mu\text{m}$
		$0.0015 \% \text{ FSO}$		$0.015 \% \text{ FSO}$
Measuring rate		switchable (software) 49.14 / 30 / 20 / 10 / 5 / 2.5 / 1.5 kHz (49.14 kHz with reduced measuring range)		
Light source		Semiconductor laser <1 mW, 405 nm (blue violet), laser class 2		
Permissible ambient light		10,000 lx		
Spot diameter	SMR	70 x 80 μm	200 x 200 μm	400 ... 500 μm
	MMR	20 x 20 μm	20 x 20 μm	400 ... 500 μm
	EMR	80 x 100 μm	200 x 400 μm	400 ... 500 μm
Protection class		IP65		
Operating temperature		0 ... +50 °C		
Storage temperature		-20 ... +70 °C		
Inputs/Outputs		Ethernet/EtherCAT RS422 analog output via C-Box		
Inputs		Laser on/off Sync/Trigger input		
Supply voltage		11 ... 30 VDC		
Power consumption		< 3 W (24 V)		
LED		status / power / Ethernet / EtherCAT		
Sensor cable	Standard	0.25 m (with connector)		
	Option	3 / 6 / 9 m with 15-pole sub-D Connector		
Synchronization		possible for simultaneous or alternating measurements		
Electromagnetic compatibility (EMC)		EN 61326-1: 2006-10 DIN EN 55011: 2007-11 (group 1. class B) EN 61 000-6-2: 2006-03		
Vibration		2 g / 20 ... 500 Hz		
Shock		15 g / 6 ms / 3 axes		
Weight (with 25cm cable)		550 g	550 g	approx. 800 g

FSO = Full Scale Output; The specified data apply to a white, diffuse reflecting surface (reference: ceramics)

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range


¹⁾ Range specifications: value in brackets is valid for a measuring rate of 49.14 kHz



	Blue Laser Technology (Blue violet laser diode 405 nm)
	Adjustable measuring rate up to 49.14 kHz
INTER FACE	Ethernet / EtherCAT / RS422 Analog output via C-Box/2A
	Advanced Real-Time-Surface-Compensation
	Calibration certificate included
	Configuration via web interface

Blue Laser Sensor for direct reflection

The optoNCDT 2300-2DR high precision laser triangulation sensor is designed for highly dynamic measurements on reflective and shiny targets. The sensor can be fixed parallel to the measurement object, which greatly simplifies the installation process. Unlike conventional laser triangulation sensors, the optoNCDT 2300-2DR uses the directly reflected light of the laser. During measurements, the blue laser light is directly reflected by the measurement object onto the receiving optics. Due to the blue laser light, the signal on the receiver element is extremely stable, which means the sensor is able to measure to nanometer resolution. An extremely small laser spot size enables the detection of very small objects.




High speed and precision on reflective, shiny surfaces

The optoNCDT 2300-2DR offers an adjustable measuring rate up to 49 kHz and so is suitable for dynamic high speed process monitoring. The new A-RTSC (Advanced Real Time Surface Compensation) feature is a development of the proven RTSC technology and enables more precise real time surface compensation when measuring onto different surface types.

The sensor is used for production control purposes such as thickness measurement of flat glass, assembly monitoring of extremely small parts and for distance measurements on annealed glass.

Compact and easy to integrate

The entire electronics is integrated in a compact sensor housing which is a worldwide unique feature of this sensor class. Data output is via Ethernet, RS422 or EtherCAT. If the sensor is operated with the C-Box/2A signal processing unit (optional), an analog output is also available. All sensor configurations are carried out via a user-friendly web interface.



Model	ILD 2300-2DR	
Measuring range ¹⁾	2 mm (1 mm)	
Start of measuring range	9 mm (9 mm)	
Mid of measuring range	10 mm (9.5 mm)	
End of measuring range	11 mm (10 mm)	
Linearity	≤ ± 0.6 μm	
	≤ ± 0.03% FSO	
Resolution (with 20 kHz)	30 nm	
	0.0015 % FSO	
Measuring rate	switchable (software) 49.14 / 30 / 20 / 10 / 5 / 2.5 / 1.5 kHz (49.14 kHz with reduced measuring range)	
Permissible ambient light	10,000 ... 40,000 lx	
Light spot diameter	SMR	21.6 x 25 μm
	MMR	8.5 x 11 μm
	EMR	22.4 x 23.7 μm
Light source	Semiconductor laser < 1 mW, 405 nm (blue violet), laser class 2	
Protection class	IP65	
Operating temperature	0 ... +50 °C	
Storage temperature	-20 ... +70 °C	
Inputs/Outputs	RS422 / Ethernet / EtherCAT	
Inputs	Laser on/off Synch / Trigger	
Supply voltage	11 ... 30 VDC	
Power consumption	< 2 W (24 V)	
Display	Status LED	off = Laser OFF red = poor target; out of range yellow = MMR green = ok
	Power LED	off = Power OFF green = Ethernet / RS422
Sensor cable	Standard	0.25 m (with connector)
	Option	3/10 m with 15-pole sub-D Connector
Electromagnetic compatibility (EMC)	according to EN 55011/12.1998 and EN 50082-2/ 02.1996	
Vibration	2 g / 20 ... 500 Hz	
Shock	15 g / 6 ms / 3 axes	

FSO = Full Scale Output

SMR = start of measuring range; MMR = midrange; EMR = end of measuring range

¹⁾ Range specifications: value in brackets is valid for a measuring rate of 49.14 kHz

Accessories for all optoNCDT Series**Power supply**

- PS 2020 (power supply 24 V / 2.5 A, input 100 - 240 VAC, output 24 VDC / 2.5 A, mounting onto symmetrical standard rail 35 mm x 7.5 mm, DIN 50022)

Controller unit for evaluation and signal conversion

- C-Box/2A (controller for conversion and evaluation of up to 2 sensor signals)

Interface card

- IF2008PCI / IF2008PCle (interface card for multiple signal processing; analog and digital interfaces)

USB converter

- IF2001/USB RS422/USB converter (converter for digital signals in USB)

USB converter

- IF2004/USB 4-channel RS422/USB converter (converter for up to 4 digital signals in USB)

Accessories for optoNCDT 1320 / 1420 / 1402CL1**Supply and output cable (drag-chain suitable)**

- PCF1420-1/I (1 m, output 4 ... 20 mA)
- PCF1420-1/I(01) (1 m, output 4...20 mA)
- PCF1420-3/I (3 m, output 4 ... 20 mA)
- PCF1420-6/I (6 m, output 4 ... 20 mA)
- PCF1420-10/I (10 m, output 4 ... 20 mA)
- PCF1420-15/I (15 m, output 4 ... 20 mA)
- PCF1420-3/U (3 m, with integrated resistor, output 1 ... 5 VDC)*
- PCF1420-6/U (6 m, with integrated resistor, output 1 ... 5 VDC)*
- PCF1420-10/U (10 m, with integrated resistor, output 1 ... 5 VDC)*
- PCF1420-15/U (15 m, with integrated resistor, output 1 ... 5 VDC)*
- PCF1420-3/IF2008 (3 m, interface and supply cable)
- PCF1420-6/IF2008 (6 m, interface and supply cable)
- PCF1420-10/IF2008 (10 m, interface and supply cable)
- PCF1420-3/C-Box (3 m)

* on request with output 2 ...10 VDC

Supply and output cable, suitable for use with robots

(available in 90° version)

- PCR 1402-3/I (3 m)
- PCR 1402-6/I (6 m)
- PCR 1402-8/I (8 m)

Accessories for optoNCDT 1610/1630**Supply and output cable**

- PC1605-3 (3 m)
- PC1605-6 (6 m)
- PC1607-5/BNC (5 m, BNC connector)

Accessories for optoNCDT**1750 / 1750LL / 1750BL / 1750DR / 1710 / 1710BL****Supply and output cable (drag-chain suitable)**

- PC1700-3 (3 m)
- PC1700-10 (10 m)
- PC1700-10/IF2008 (10 m, for use with interface card IF2008)
- PC1750-3/C-Box (3 m)
- PC1750-6/C-Box (6 m)
- PC1750-9/C-Box (9 m)

Supply and output cable (suitable for use with robots)

- PCR1700-5 (5 m)
- PCR1700-10 (10 m)

Supply and output cables for temperatures up to 200 °C

- PC1700-3/OE/HT (3 m)
- PC1700-6/OE/HT (6 m)
- PC1700-15/OE/HT (15 m)

Protection housing

- SGH model (sizes S and M)
- SGHF model (sizes S and M)
- SGHF-HT model

Accessories for optoNCDT**2300 / 2300LL / 2300BL / 2300-2DR****Supply and output cable**


- PC2300-0,5Y (connection cable to PC or PLC; for operation a PC2300-3/SUB-D will be required)
 - PC2300-3/SUB-D (3 m; for operation a PC2300-0,5Y will be required)
 - PC2300-3/IF2008 (interface and supply cable)
 - PC2300-3/OE (3 m)
 - PC2300-6/OE (6 m)
 - PC2300-9/OE (9 m)
 - PC2300-15/OE (15 m)
 - PC2300-3/C-Box/RJ45 (3 m)
- * other cable lengths on request

Protection housing

- SGH model (sizes S and M)
- SGHF model (sizes S and M)
- SGHF-HT model

Supply and output cables for temperatures up to 200 °C

- PC2300-3/OE/HT (3 m)
- PC2300-6/OE/HT (6 m)
- PC2300-9/OE/HT (9 m)
- PC2300-15/OE/HT (15 m)



optoNCDT Demo Tool

The scope of supply includes a software for easy sensor configuration. The settings can be implemented conveniently via a Windows user interface on the PC. The sensor parameters are transmitted to the sensor via the serial port and can also be saved if required. The software is available as single and multi-channel version. The sensor is connected to the PC via the sensor cable using a USB converter. [for any ILD sensor]

Free download

Download free of charge from www.micro-epsilon.com/download: software, driver and well-documented driver DLL for easy sensor integration in existing or customer software.

Protection housing for harsh environments

To protect the laser sensors in extreme environments, individual protective housings are available for all sensor models. There are three different models:

SGH model:

Completely enclosed housing with an integrated front window, where the sensor measures through the window. The water-resistant housing provides protection against solvents and detergents.

SGHF model:

With window and compressed-air connection ideal for high ambient temperatures. The integrated air cooling of the housing offers optimum protection for the sensor.

SGHF-HT model

This water-cooled protection housing with window and compressed-air connection is designed for measurement tasks in ambient temperatures up to 200 °C.

Suitable for all long-range sensors

optoNCDT 1710

optoNCDT 1750-500 and optoNCDT 1750-750

optoNCDT 2310

optoNCDT 2300 - 200

Maximum ambient temperature 200 °C

Maximum temperature of cooling water $T(\max) = 10\text{ °C}$

Minimum water flow rate $Q(\min) = 3\text{ liters/min}$



SGHx ILD size S (140x140x71 mm)
for optoNCDT 1750 / 2300 dimensions 97x75 mm

SGHx ILD size M (140x180x71 mm)
for optoNCDT 1750 / 2300 dimensions 150x80 mm




IF2008PCI/IF2008 PCIe - PCI Interface card

The IF2008 interface card is designed for installation in PCs and enables the synchronous capture of four digital sensor signals and two encoders. The IF2008E expansion board enables the acquisition of two digital sensor signals, two analog sensor signals and eight I/O signals. The absolutely synchronous data acquisition plays an important role particularly for planarity or thickness measurement tasks. The data are stored in a FIFO memory in order to enable resource-saving processing in blocks in the PC.

Special features

- 4x digital signals and 2x encoders with IF2008 basic PCB
- 2x digital signals, 2x analog signals and 8x I/O signals with IF2008E expansion board
- 6x digital signals, 2x encoders, 2x analog signals and 8x I/O signals together with IF2008E
- FIFO data memory
- Synchronous data acquisition



Interface card IF2008, IF2008E for individual signal processing

IF2001/USB converter RS422 to USB

The RS422/USB converter transforms digital signals from a laser-optical sensor into a USB data packet. The sensor and the converter are connected via the RS422 interface of the converter. Data output is done via USB interface. The converter loops through further signals and functions such as laser on/off, switch signals and function output. The connected sensors and the converter can be programmed through software.



IF2004/USB: 4-channel converter from RS422 to USB

The RS422/USB converter is used for transforming digital signals from up to four optical sensors into USB data signals. The converter has four trigger inputs and a trigger output for connecting additional converters. Data is output via an USB interface. The connected sensors and the converter can be programmed through software.

Special features

- 4x digital signals via RS422
- 4x trigger inputs, 1x trigger output
- Synchronous data acquisition
- Data output via USB



C-Box/2A Controller for conversion and evaluation of up to two sensor signals

C-Box/2A is used for fast D/A conversion of two digital input signals or for evaluating two digital sensor signals. The controller is compatible with the optoNCDT 2300 laser triangulation sensors. Output of the sensor signals is possible via two configurable analog outputs, Ethernet or USB. Handling of the C-Box/2A and of the connected sensors are performed via web interface. Averaging functions, thickness, diameter, step and inclinations can be calculated. The D/A conversion is executed at 16 bit and max. 70 kHz.



Sensors and Systems from Micro-Epsilon



Sensors and systems for displacement, distance and position



Sensors and measurement devices for non-contact temperature measurement




Measuring and inspection systems for metal strips, plastics and rubber



Optical micrometers and fiber optics, measuring and test amplifiers



Color recognition sensors, LED analyzers and inline color spectrometers



3D measurement technology for dimensional testing and surface inspection