



More Precision

thermoMETER
Non-contact IR temperature sensors





thermoMETER CTtrans

CTtrans is a compact material analysis system to measure transmissivity, emissivity or degree of reflection. The system uses an active infrared transmitter in combination with an IR CT detector. A programmable controller with display processes the measurement data and outputs the information analogue or digitally.


- Combination of miniaturised infrared radiator and CT - infrared sensor
- Different modes for evaluation of the material parameters transmissivity, emissivity and reflection
- 0-10V - output allows transmission of the determined emissivity to a CT sensor
- Infrared temperature measurement with automatic material detection
- Available as a mobile system (with carrying case) or for fixed installations
- High life span of the infrared source (40.000h operating time)



Emissivity




Transmissivity



Online detection of emissivity and transmissivity

If material changes the new emissivity and transmissivity will be determined by the CTtrans and transferred via 0-10V output to the CT connected for temperature measurement.



Product identification

CTT - SF15 - C3
 Cable length 3m
 SF=Standard Focus
 thermoMETER CTtrans

Model		CTT-SF15-C3
Spectral range		8 to 14 μ m
Repeatability ¹		\pm 2,5%
Probe size		>7mm
Emissivity		10 to 100%
Transmissivity/gain		0 to 100%
Reflexion		0 to 100%
Measurement cycle		0.1 to 99s
Recommended distance (IR source - sensor)		30 to 60mm
Outputs/analogue		0/4 to 20mA, 0 to 5/10V
Output/digital		3.3V / 30mA
Relay output	optional	2 x 60VDC / 42VAC _{eff} ; 0.4A; optically isolated
Outputs/digital	optional	USB, RS232, RS485 (optional)
Output impedances	current output	mA max. 500 Ω (8 to 36VDC)
	voltage output	mV min. 100k Ω load impedance thermocouple 20 Ω
Input/digital		calibration input
Cable length		3m (standard)
Power supply		10 to 24VDC; max. 150mA
Environmental rating		IP 65 (NEMA-4)
Ambient temperature		sensor: -20°C to 100°C IR source: -20°C to 100°C
Storage temperature		sensor: -40°C to 120°C IR source: -40°C to 120°C
Relative humidity		10 to 95%, non condensing
Vibration		IEC 68-2-6: 3G, 11 to 200Hz, any axis
Shock		IEC 68-2-27: 50G, 11ms, any axis
Weight		sensor: 40g; IR source: 40g; controller: 450g

¹ \pm ambient temperature: 23 \pm 5°C

Scope of supply

- ▶ CT 15:1 sensor
- ▶ IR source
- ▶ CTtrans controller
- ▶ Power supply (AA-batteries)
- ▶ Adjustment board
- ▶ Manual
- ▶ Case

High performance sensors made by Micro-Epsilon




Sensors and systems for displacement and position



Sensors and measurement devices for non-contact temperature measurement



2D/3D profile sensors (laser scanner)



Measurement and inspection systems for quality assurance



Optical micrometers, fibre optic sensors and optical fibres



Colour recognition sensors, LED analysers and colour online spectrometer



MICRO-EPSILON Headquarters
Koenigbacher Str. 15 · 94496 Ortenburg / Germany
Tel. +49 (0) 8542 / 168-0 · Fax +49 (0) 8542 / 168-90
info@micro-epsilon.com · www.micro-epsilon.com

MICRO-EPSILON UK Ltd.
No.1 Shorelines Building · Shore Road · Birkenhead · CH41 1AU
Phone +44 (0) 151 355 6070 · Fax +44 (0) 151 355 6075
info@micro-epsilon.co.uk · www.micro-epsilon.co.uk